Ref #	Hits	Search Query	DBs	Default Operat or	Plural s	Time Stamp
LI	13	(insulat\$5 near3 (bridge link arm leg piece part)) near4 (beam bar rod) near4 (actuat\$3 motor)	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:29
L2	0	((microelectro\$8 near6 (strain near4 (gauge gage detect\$4 indicat\$5 monitor\$5 transducer))) and (insulat\$5 near3 (bridge link arm leg piece part)) near6 (beam bar rod) near4 (actuat\$3 motor))	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:33
L3	0	((microelectro\$8 near6 (strain near4 (gauge gage detect\$4 indicat\$5 monitor\$5 transducer))) and (insulat\$5 near3 (bridge link arm leg piece part)) and (beam bar rod) near4 (actuat\$3 motor))	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:33
L4	0	((microelectro\$8 near6 (strain near4 (gauge gage detect\$4 indicat\$5 monitor\$5 transducer))) and (insulat\$5 near3 (bridge link arm leg piece part)) and (beam bar rod) and (actuat\$3 motor))	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:33
L5	38	((strain near4 (gauge gage detect\$4 indicat\$5 monitor\$5 transducer)) and (insulat\$5 near3 (bridge link arm leg piece part)) and (beam bar rod) and (actuat\$3 motor))	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:33
L6	0	(actuat\$4 motor) near5 (insulat\$5 near3 (bridge link arm leg)) near5 (detect\$5 sens\$5 indicat\$5 gage gauge transducer)	US-PGPU B, USPAT; EPO, JPO	OR	OFF	2005/10/31 09:36
L7	0	(actuat\$4 motor) near6 (insulat\$5 near3 (bridge link arm leg)) near6 (detect\$5 sens\$5 indicat\$5 gage gauge transducer)	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:36

L8	5	(actuat\$4 motor) near6 (insulat\$5 near6 (bridge link arm leg)) near6 (detect\$5 sens\$5 indicat\$5 gage gauge transducer)	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:38
L9	259	73/781.ccls.	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:38
L10	343	73/862.59.ccls.	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:38
L11	325	73/777.ccls.	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:38

Ref #	Hits	Search Query	DBs	Default Operat or	Plural s	Time Stamp
L5	38	((strain near4 (gauge gage detect\$4 indicat\$5 monitor\$5 transducer)) and (insulat\$5 near3 (bridge link arm leg piece part)) and (beam bar rod) and (actuat\$3 motor))	US-PGPU B; USPAT; EPO; JPO	OR	OFF	2005/10/31 09:33